

New Quad DVB-T2/T or DVB-C  
transmodulators with double slot C.I.  
Flexmode and USB playin

**3DG-4T2-BP**

**3DGFLEX Evo**



The new **3DGFlex Evo** professional headend will introduce many innovative features.

**Extreme flexibility!!** One of the most innovative features of the new generation modules is the "Smart & Pool" function: all the new modules inserted on the same 3DGBOX exchange between them bidirectionally the contents through the very high speed Back Panel interface (up to 1Gbit/s bidirectional).

In this way each new 3DG "Evo" module is able to manage the signals coming from all the other new modules, with the advantage of being able to create flexible configurations, optimizing the number of elements of the system, especially in case of complex installations.

Also the "**backward compatibility**" concept is very advantageous: the new EVO modules can be managed on the same 3DG-BOX together with the "twin" existing modules (for ex. 3DG-2T2-2T), thus ensuring maximum comfort during the network design. In this way the installer could deploy many digital contents through every MATV coaxial network.

**3DG-4T2-BP (without output modulators)** allow to add "reception's capability" on the complete headend system. The module is able to tune up to 4 independent HD or SD DTT multiplexes (or DVB-C cable digital signals), decrypt the content and "pool" all the programs to the other new modules inserted on the same 3DG-BOX through the very high speed Back Panel (i.e. "Smart&Pool").

**NEW FEATURES:** 3DG-4T2-BP are equipped with two universal slots Common Interface each module that can be used on FlexCAM operation mode. With the 3DGFlex EVO new generation modules is now possible to manage even the external Audio/Video file playback stored, for ex, in the USB pendrive (.TS file format).

## Main Specifications

---

- **Multi Inputs:** independent DTT inputs (DVBT2/T or DVB-C – demodulation standard selectable during the setup), “USB input” for external playback content management and Back-Panel in/out (programs shared between the new modules inserted on 3DG-BOX).
- **4xDVB-T or 4xDVB-C output multiplexes** (two pairs of adjacent digital modulators) on 3DG-4T2-4T version
- **2 Common Interface slots and Optimized CAMs Management:** the new 3DG-EVO modules allows to manage both CAMs modules in two different operation modes:
  - **FlexCAM mode:** it can be forwarded to the same CAM module the programs coming from any RF input (i.e. Flexible CAM on the OUTPUT)
  - **STANDARD mode:** each CAM module can be associated with a RF input in order to decrypt the encoded programs coming only from this specific input.
- **New “Smart&Pool”** it’s possible to manage up to 1Gbit/s bidirectional data throughput between all the modules inserted into the headend. (3DGFlex evolution family)
- 3DGFlex-Evo backwards compatibility: in this way it’s possible to maintain the old modules or use the new modules into the same 3DG-Box
- **ARP 2.0** = Automatic Recovery Procedure to save the higher priority programs and guarantee Continuity of Service when bit rate overflows occur. All the program are sequentially restored when the global bit rate returns within the limits.
- **AUTO REMAPPING function:** you can change in real time the program inside the mux without rescanning all the TV set along the network.
- **USB Port** to upload/download pre-setted set up or for the firmware upgrade, external audio/video file’s playback (.TS file format).
- **DVB-T/DVB-C “agile output modulation” selectable via sw on 3DG-4T2-4T** transmodulator: one product to fit every coax network distribution.
- **WEB interface based headend: today is even more intuitive.** The headend setup, and configuration must be done by using the improved web interface built-in; basic setup available by on board keyboard.
- **“Mux-ad-Hoc”:** you can create the available muxes by choosing the programs tuned from all the new modules inserted on a same BOX and manage all the descriptor parameters of each mux (ONID, TSID, NetID,...) and each program inside the mux (LCN, SID, PID, Programname..)
- **Multi PLP “ready”:** management of MULTI PLP programs.

PRODUCT		3DG-4S2-BP	
Fracarro code		283166	
Front-End			
N° input	N°	4 (independents)	
Input frequency	MHz	110÷862	
Input level	dBµV	45÷85 (DVB-T2)	
Input step tuning	MHz	50	
Impedence	OHm	75	
Remote power supply	Vdc, mA	12, 200 – 24, 100	
AFC Range	KHz	±400 (DVB-T2/T), ±100 (DVB-C)	
Back Panel In/Out			
Max bitrate	Mbit/s	1000 (bidirectional)	1000 (bidirectional)
Connector		48 pin on back-panel	48 pin on back-panel
General features			
Power consumption	W	12 (typ. with CAMs)	
Connectors	Type	F female (RF), USB (fw upgrade, TS video file playback)	
Common Interface		2 x PCMCIA (Standard EN50221, TS10169) , FlexCAM or STANDARD mode	
Dimensions (L.x W.x H)	mm	245x208x54	
Operating temperature	°C	-5 ÷ +50 (without CAMs)	
Compliant		The full text of the EU declaration of conformity is available at the following internet address:	