

## 2 Way Splitter 5-2400MHz

### SPTR2

SKU : AA0702ACX0801



**2 way splitter** on frequency range **5-2400MHz** with “top down” F connectors.

**Compact** and good-looking design to fulfill every installation requirement and enable them to be installed in every location.

**Zinc die cast housing** allows to reach the best performances over all the operating frequency range, with low insertion loss up to high frequencies and high isolation between outputs.

DC pass is allowed between every output and input.

### Main Specifications

- Low insertion loss also on SAT band, up to 2400MHz.
- Changeless attenuation on output ports from 5 to 2400MHz.
- DC pass from outputs to input
- High return loss
- “A” shielding factor
- 2 earth screws
- Wall fixing

SPLITTERS											
Code	Item	Insertion Loss					Separation Out-Out				
		40 MHz	862 MHz	950 MHz	2150 MHz	2400 MHz	40 MHz	862 MHz	950 MHz	2150 MHz	2400 MHz
		dB	dB	dB	dB	dB	dB	dB	dB	dB	dB
287305	SPTR2	3,5	4	4	5	5.5	27,5	20	20	18	18

Fracarro Code	Fracarro Code	Product dimensions mm	Packing	EAN Code	Quantity PC	Packaging dimensions mm	Net Weight	Weight kg.
287305	SPTR2	55x60x25	Multiple	8.01698E+12	10	112x127x64	0.82	0.9