


6 Way Splitter 5-2400MHz

SPTR6

SKU : AA0706ANX0801



6 way splitter on frequency range **5-2400MHz** with “top down” F connectors.

Compact and good-looking design to fulfill every installation requirement and enable them to be installed in every location.

Zinc die cast housing allows to reach the best performances over all the operating frequency range, with low insertion loss up to high frequencies and high isolation between outputs.

DC pass is allowed between every output and input.

Main Specifications

- Low insertion loss also on SAT band, up to 2400MHz.
- Changeless attenuation on output ports from 5 to 2400MHz.
- DC pass from outputs to input
- High return loss
- “A” shielding factor
- 2 earth screws
- Wall fixing

SPLITTERS											
Code	Item	Insertion Loss					Separation Out-Out				
		40 MHz	862 MHz	950 MHz	2150 MHz	2400 MHz	40 MHz	862 MHz	950 MHz	2150 MHz	2400 MHz
		dB	dB	dB	dB	dB	dB	dB	dB	dB	dB
287308	SPTR6	10	11	11,5	14,5	16	27,5	25	25	25	25

Fracarro Code	Fracarro Code	Product dimensions mm	Packing	EAN Code	Quantity PC	Packaging dimensions mm	Net Weight	Weight kg.
287308	SPTR6	100x60x25	Multiple	801697809499	10	122x254x64	1.43	1.50