

### **Key Features**

### Smart Platform



#### Quad Core SoC\*

The High Performance SoC can execute several tasks at the same time and provides smooth content playback.



\*SoC : System-on-Chip

#### webOS 2.0

The webOS 2.0 platform provides easy and convenient tools to create contents. LG's SDK\* and technical supports make content development and management easier.



\*Software Development Kit

#### Simple Installation

Installation has been simplified by removing the external media player and Ethernet/RS232C cables.



Built-in Wi-Fi: (removing Ethernet or RS232C cables) 802.11n (2.4GHz/5GHz)

# Connectivity Supports



#### Simple Network Management Protocol

SNMP support ensures convenient network management.



#### Mirroring

Content sharing is more convenient on a Wi-Fi network.



#### **SoftAP**

The 22SM3B with SoftAP software can operate as a wireless access point for mobile devices.



#### Easy Maintenance



#### **Real-Time Remote Monitoring**

When an alarm occurs, an e-mail notification is sent using SuperSign C or SI SW through the SNMP Protocol. In case of malfunctions or errors, real-time remote care is available.



## Supportive Convenience

#### BEACON

With BEACON and Bluetooth Low Energy (BLE) supported by 22SM3B, retail stores can provide coupons and information in real-time.





## **Intuitive Information Delivery**



Screen Size

22

22SM3B

• Brightness : 250 cd/m<sup>2</sup>

• Bezel : Top/Left/Right/Bottom 16.3mm (Even Bezel)

• Depth : 53.8mm

• Interface : HDMI / USB / RGB / RJ45 / IR

✓IPS webOS 2.0






Specification	ons	22SM3B
PANEL	Screen Size	21.5
	Panel Technology	IPS
	Aspect Ratio	16:9
	Native Resolution	1,920 x 1,080 (FHD)
	Brightness	250cd/m <sup>2</sup>
	Contrast Ratio	1,000:1
	Dynamic CR	4,000,000:1
	Viewing Angle (H x V)	178×178
	Surface Treatment	Hard coating (3H), Anti-glare treatment of the front polarizer (Haze 1%(Typ.))
	Guaranteed Operating Hour	18 Hours
	Orientation	Portrait & Landscape
CONNECTIVITY	Input	HDMI, RGB, Audio, USB 3.0, SD card
	Output	External Speaker (L/R)
	External Control	RS232C In, IR Receiver, Pixel Sensor
PHYSICAL SPECIFICATION	Bezel Color	Black
	Bezel Width	16.3mm (T/R/L/B)
	Monitor Dimension (W x H x D)	510.3 x 302.1 x 53.8 mm
	Weight (Head)	3.6kg
	Carton Dimensions (W x H x D)	565 x 357 x 103 mm
	Packed Weight	4.7kg
	VESA <sup>™</sup> Standard Mount Interface	100 x 100
SPECIAL FEATURES		ISM Method, Internal Memory (4GB), Wi-Fi (802.11n combo built-in), USB Cloning, Local contents scheduling, Sync Mode, PM Mode Local Time Auto Setting, Wake on LAN, Pivot Mode, Content Rotation 0,90,270, Fail Over, BEACON On/Off, Embedded Template
ENVIRONMENTAL CONDITIONS	Operating Temperature Range	0 °C to 40 °C
	Operating Humidity Range	10 % to 80 %
POWER	Power Supply	100-240V~, 50/60Hz
	Power Type	Built-In Power
	Power Typ.	35W
	Consumption Smart Enegy Saving	On 25.13W / Off 29.76W
STANDARD (CERTIFICATION)	Safety	UL / cUL / CB / TUV
	EMC	FCC Class "B" / CE
SOFTWARE COMPATIBILITY	SuperSign-W / Lite	Yes
	SuperSign-C	Yes
ACCESSORY	Basic	Remote Controller (include 2ea batteries), Power Cord, QSG, RGB Cable, Phone to RS232C Gender
	Optional	Pixel sensor (KT-SP0)

### Dimension (unit:mm)


22"

510.3 x 302.1 x 53.8 /

3.6kg







## Connectivity

1 RS-232C IN

**5** RGB IN

2 AUDIO IN

6 HDMI IN

3 PIXEL SENSOR

**1** USB 3.0

**Q**LAN **HDMI** 

## Download LG Commercial Display Mobile App





More info www.lgecommercial.com





