

Outstanding Clarity and Uniformity

SH7PE-H

The SH7PE-H series creates entertaining and memorable experiences for customers while delivering clear and vivid content under brightly lit locations. Its built-in OPS power enables a single cable connection and a tidy appearance, which is especially important in places with heavy foot traffic, such as airports, train stations, or QSRs.




Outstanding Clarity and Uniformity

SH7PE-H

Superior Picture Quality


Clear View with Non-glare Coating

Viewers can be annoyed by unnecessary reflections when watching a screen under brightly lit conditions. The SH7PE-H series has resolved such inconveniences by increasing the level of haze, which enhances visibility and text readability.



High Visibility

The 700 cd/m² brightness is enough to stand out against the surrounding background, so the display can attract passerby and delivers content vividly and effectively under brightly lit condition.




Outstanding Clarity and Uniformity

SH7PE-H

Tidy Appearance

A Single Cable for OPS/Display


The SH7PE-H series is a OPS* built-in power model. The power for both OPS player and the display is provided through a single cable, enabling a sleek look with a slimmer structure.



* OPS: Open Pluggable Specification

Easy Cable Management

The well-organized cable terminals and holes in the back help make managing cables easy, and give a neat and tidy appearance.



Outstanding Clarity and Uniformity

SH7PE-H

Reliable Operation

Lower Electromagnetic Waves

The SH7PE series complies with 'EMC Class B', which ensures lower electromagnetic wave emission, fostering a more pleasant environment for customers who spend long hours in places such as airports.



Conformal Coating

The product can be often unavoidably exposed to dust and water during maintenance. Conformal coating on major circuit board eliminates such circumstances by protecting it against dust, iron powder, humidity, etc.




Outstanding Clarity and Uniformity

SH7PE-H

User Convenience

Intuitive Menu for Digital Signage

SH7PE series has enhanced its UX by applying dedicated menu tailored to commercial requirements. With an all-in-one home menu and all signage-related functions indexed in the setting, you can easily check and access the menu using a remote controller.




Detachable Logo & Built-in Speaker

The detachable logo makes it easy for the user to arrange the signage. Also, sounds can be played from built-in speakers, offering viewers various multi-media experiences.




Dimension (unit: mm)


55"



49"




43"



Connectivity

55" / 49" / 43"



- 1 RS232C IN
- 2 RS232C OUT
- 3 HDMI IN
- 4 AUDIO OUT

- 5 EXT IR IN
- 6 DVI-D IN
- 7 RGB IN
- 8 LAN

- 9 AUDIO IN
- 10 USB



Specifications

		55SH7PE-H	49SH7PE-H	43SH7PE-H
PANEL	Screen Size	55"	49"	43"
	Panel Technology	IPS	IPS	IPS
	Aspect Ratio	16 : 9	16 : 9	16 : 9
	Native Resolution	1,920 x 1,080 (FHD)	1,920 x 1,080 (FHD)	1,920 x 1,080 (FHD)
	Brightness	700 cd/m ² (Max.), 665 cd/m ² (Typ.)	700 cd/m ² (Max.), 665 cd/m ² (Typ.)	700 cd/m ² (Max.), 665 cd/m ² (Typ.)
	Viewing Angle (H x V)	178 x 178	178 x 178	178 x 178
	Response Time	12 ms	12 ms	12 ms
	Surface Treatment (Typ.)	Haze 28%	Haze 28%	Haze 28%
	Life time (Typ.)	50,000 Hrs	50,000 Hrs	50,000 Hrs
CONNECTIVITY	Operation Hours	24 Hrs	24 Hrs	24 Hrs
	Orientation	Landscape & Portrait	Landscape & Portrait	Landscape & Portrait
	Input	HDMI (2), DVI-D, RGB, Audio, USB	HDMI (2), DVI-D, RGB, Audio, USB	HDMI (2), DVI-D, RGB, Audio, USB
	Output	Audio (Off/Fixed/Variable)	Audio (Off/Fixed/Variable)	Audio (Off/Fixed/Variable)
MECHANICAL SPECIFICATION	External Control	RS232C In/out, RJ45 In, IR In	RS232C In/out, RJ45 In, IR In	RS232C In/out, RJ45 In, IR In
	Bezel Color	Black	Black	Black
	Bezel Width	11.9 mm (T/R/L), 18 mm (B)	11.9 mm (T/R/L), 18 mm (B)	11.9 mm (T/R/L), 18 mm (B)
	Monitor Dimension (W x H x D)	1,238 x 714.9 x 54 mm	1,102.2 x 638.5 x 54 mm	969.6 x 563.9 x 54 mm
	Weight (Head)	17.5 kg	14.3 kg	10.5 kg
	Monitor with Optional Stand Dimensions (W x H x D)	1,238 x 773.4 x 219.6 mm	1,102.2 x 696.8 x 219.6 mm	969.6 x 622.2 x 193 mm
	Weight (Head+Stand)	20.8 kg	17.6 kg	13.0 kg
	Carton Dimensions (W x H x D)	1,330 x 807 x 170 mm	1,197 x 760 x 166 mm	1,052 x 650 x 123 mm
	Packed Weight	21.7 kg	17.4 kg	12.6 kg
KEY FEATURE	VESA™ Standard Mount Interface	300 x 300 mm	300 x 300 mm	200 x 200 mm
		OPS Power Built-in, Wi-Fi Dongle Ready, Temperature Sensor, Auto Brightness Sensor, Pixel Sensor, Power Indicator, Local Key Operation, USB Auto Playback, Local Contents Scheduling, Failover Image Customization (Bootting Logo/No Signal), Firmware Update by Network, Tile Mode, SNMP, ISM Mode, Crestron Connected®, DPM, HDMI-CEC**, Built-in Speaker (10W+10W)		
ENVIRONMENTAL CONDITIONS	Operation Temperature	0°C to 40°C	0°C to 40°C	0°C to 40°C
	Operation Humidity	10% to 80%	10% to 80%	10% to 80%
POWER	Power Type	100-240V~, 50/60Hz	100-240V~, 50/60Hz	100-240V~, 50/60Hz
	Power Supply	Built-In Power	Built-In Power	Built-In Power
	Power Typ. / Max.	95 W / 140 W	85 W / 130 W	75 W / 115 W
	Consumption Smart Energy Saving	66.5 W	59.5 W	52.5 W
CERTIFICATION	Safety	IEC 60950-1 / EN 60950-1 / UL 60950-1	IEC 60950-1 / EN 60950-1 / UL 60950-1	IEC 60950-1 / EN 60950-1 / UL 60950-1
	EMC	FCC Class "B" / CE / KC	FCC Class "B" / CE / KC	FCC Class "B" / CE / KC
	ErP / Energy Star	Yes (N/A for EU) / Yes (Energy Star 7.0)	Yes (N/A for EU) / Yes (Energy Star 7.0)	Yes (N/A for EU) / Yes (Energy Star 7.0)
MEDIA PLAYER COMPATIBILITY	OPS Type Compatible	Yes	Yes	Yes
	External Media Player Attachable	Yes (MP500/MP700)	Yes (MP500/MP700)	Yes (MP500/MP700)
SOFTWARE COMPATIBILITY	Content Management Software	SuperSign CMS	SuperSign CMS	SuperSign CMS
	Control and Monitoring Software	SuperSign Control+ / Control	SuperSign Control+ / Control	SuperSign Control+ / Control
ACCESSORIES	Basic	Remote Controller (2ea Batteries Included), Power Cord, QSG, RGB Cable, Regulation Book, Phone to RS232C Gender, IR Receiver		
	Optional	Stand (ST-492T), Media Player, Wall Bracket (LSW350B), VESA Adapter (AM-B330S), Wi-Fi Dongle (AN-WF500), Touch Overlay (KT-T55E), OPS Kit (KT-OPSD)	Stand (ST-492T), Media Player, Wall Bracket (LSW350B), VESA Adapter (AM-B330S), Wi-Fi Dongle (AN-WF500), Touch Overlay (KT-T49E), OPS Kit (KT-OPSD)	Stand (ST-432T), Media Player, Wall Bracket (LSW230B), VESA Adapter (AM-B220S), Wi-Fi Dongle (AN-WF500), Touch Overlay (KT-T43E), OPS Kit (KT-OPSD)

* Network Based Control ** Compatibility may differ by equipment.



Download
LG Information Display
Mobile App

Google Play Store

www.lg.com/b2b

www.youtube.com/c/LGCommercialDisplay

www.facebook.com/LGInformationDisplay

www.linkedin.com/company/LGInformationDisplay

LG may make changes to specifications and product descriptions without notice.

Copyright © 2018 LG Electronics Inc. All rights reserved. "LG Life's Good" is a registered trademark of LG Corp.
The names of products and brands mentioned here may be the trademarks of their respective owners.

