

## Cascade Msw 9 IN A/P TV SWI932TS



The SWI9xxTS Serie belongs to the cascade multiswitch range with 9 inputs (8 satellite polarities and TV); it was designed to fulfil every installation requirement in small and medium distribution systems.

The product ensures high quality in a compact size, its inputs are distinguished by different colours to make the cable connection faster and easier.

The serie is composed by 5 products: 9 inputs with 8, 12, 16, 24 and 32 output taps; each port has a LED which shows the correct reception of the STB DiSEqC command.

The product can be used with SWA930TS amplifier, which allows to adjust appropriately the satellite and TV gains

### Main Specifications

- Dip switch to select TV gain active and passive
- Return channel included when TV gain is passive
- Satellite bandwidth up to 2300MHz
- High output level
- Easy to install thanks to standard colour coding
- Low cost
- Compact size

PRODUCT		SWI932TS
Fracarro Code		287364
Inputs		
Outputs		32
Satellite		
Bandwidth	MHz	950 - 2300
Gain	dB	-2
Uptilt	dB	4
Insertion Loss	dB	-4
Max Output Level (IM3)	dBμV	100
Return Loss	dB	10
Terrestrial		
Bandwidth	MHz	50-862

Gain Active	dB	-6
Gain Passive	dB	-26
Insertion Loss	dB	-6
Max Output Level (IM3)	dB $\mu$ V	95
Return Loss	dB	10
General Parameters		
Isolation SAT/SAT TV/SAT	dB	30
Standard	V, KHz	14/18 0/22 - DiSEqC 2.0
Tap Consumption	mA	50
Trunk Consumption(@13V)	mA	160 (TV Active)
DC Plug	mm	2.1x5.5x12
	pol	internal positive, external negative
Max current to LNB	mA	1500
Dimensions	mm	300x190x40
Operating Temperature	$^{\circ}$ C	0 $\div$ 40

Code	Item	Packaging	Quantity	Dimensions	Net Weight	Weight
			pcs	mm	kg	kg
287364	SWI932TS	Single	1	330x245x55	1.2	1.2

